

CZT

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER'S PART NO. _____ REV. _____

DESCRIPTION RJ45+2USB3.0 ICM(1000Base-T 1Port)

CZT'S PART NO. JBG110741011 REV. C

ISSUE NO. _____

ISSUE DATE APR.02,2020

<input type="checkbox"/> APPROVED	<input type="checkbox"/> REJECTED:
<input type="checkbox"/> APPROVED UNDER THE CONDITIONS:	

SuZhou Yihua Communicated Connector Co., Ltd.

Add: No.1558, Linhu East Road, Foho New&Hi-tech industrial Development Zone,
Wujiang,Jiangsu,P.R.C.

TEL:+86-512-82078810

FAX:+86-512-82078858

DongGuan Yizhao Electronic Co., Ltd.

Add: Yihua Holdings Industrial park, Cuntou district, Hu'men Town,
Dongguan,Guangdong,P.R.C.

TEL:+86-769-8624 0111

FAX:+86-769-8624 0238




Note:

1. This specification is the proprietary of Yihua Communicated Connector Co., Ltd. and is not allowed to be revealed to third party without any written approval.
2. This specification is valid within 1 year before approval, and for any updated specification information required, please contact with CZT's sales window before order releases.

CZT

SPECIFICATION FOR APPROVAL

2. Revision Change Record

Customer Part No.: CZT Part No.: JBG110741011 Part Name: RJ45+2USB3.0 ICM(1000Base-T 1Port)					Rev.: C
					
Rev	Description	Drawn	Designed	Approved	Issue Date
A	Specification issued	ChenLingjuan	ZhangChao	Topup.Liu	APR.11 2016
B	Change From: 5-1. Label: Plug In Side 	ChenLingjuan	ZhangChao	Topup.Liu	AUG.31 2018
	To: 5-1. Label: Plug In Side 				
C	Change From: SHIELD:SUS304&BRASS To: FRONT SHIELD:SUS304 BACK SHIELD:BRASS, PREPLATED WITH 30 MICRO-INCHS	ChenLingjuan	ZhangChao	Topup.Liu	APR.02 2020

CZT

SPECIFICATION FOR APPROVAL




Customer Part No.:
CZT Part No.: JBG110741011
Part Name: RJ45+2USB3.0 ICM(1000Base-T 1Port)

Rev.: C



4. Mechanical Dimension and Notes:

4-1. Mechanical Dimension:



UNIT : mm / inch

A = 18.95 / 0.746

B = 30.87 / 1.215

C = 27.85 MAX

D = 3.20 / 0.126

Unless otherwise specified, all dimensions tolerances is ± 0.254 / 0.010.

4-2. Notes:

1. CONNECTOR MATERIAL:

1.1 RJ45

HOUSING: THERMOPLASTIC BLACK UL94 V-0

FRONT SHIELD: SUS304

BACK SHIELD: BRASS, PREPLATED WITH 30 MICRO-INCHES

CONTACT: PHOSPHOR BRONZE

CONTACT PLATING: SELECTIVE GOLD, 50 MICRO-INCHES MIN IN CONTACT AREA

1.2 USB3.0

HOUSING: THERMOPLASTIC BLUE UL94 V-0

SHIELD: BRASS

SHIELD PLATING: NICKEL

CONTACT: PHOSPHOR BRONZE

CONTACT PLATING: SELECTIVE GOLD, 30 MICRO-INCHES MIN IN CONTACT AREA

2. PIN NOT ELECTRICALLY CONNECTED MAYBE OMITTED SEE ELECTRICAL DRAWING FOR OMITTED PINS

3. RJ45 CAVITIES CONFORM TO FCC RULES AND REGULATION PART 68.

4. THE PART IS RECOMMENDED FOR WAVE SOLDERING PROCESS PEAK SOLDERING TEMPERATURE IS 260° C MAX, 10 SECS MAX

5. OPERATING TEMPERATURE T=0° C TO +70° C.

6. STORAGE TEMPERATURE T=-40° C TO +85° C.

LED SPECIFICATION				
STANDARD LED	WAVELENGTH	Forward Current	Forward V(max)	TYP
GREEN	565nm	20 mA	2.4V	2.2V
YELLOW	590nm	20 mA	2.5V	2.1V

Drawn by
ChenLingjuan

Designed by
ZhangChao

Approved by
Topup.Liu

CZT

SPECIFICATION FOR APPROVAL

Customer Part No.:
CZT Part No.: JBG110741011
Part Name: RJ45+2USB3.0 ICM(1000Base-T 1Port)

Rev.: C




5. Label and Recommended PWB Layout and Suggested Panel Opening:
5-1. Label:

Plug In Side



- 5-2. Suggested Panel Opening:



UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

REFERENCE ONLY

CZT

SPECIFICATION FOR APPROVAL


Customer Part No.:
CZT Part No.: JBG110741011
Part Name: RJ45+2USB3.0 ICM(1000Base-T 1Port)

Rev.: C



5-3. Keep-Out Area (Component Side View):


Connector Boundary



UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

Plug In Side

5-4. Recommended PWB Layout (Component Side View):



UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

Plug In Side

CZT

SPECIFICATION FOR APPROVAL


Customer Part No.:
CZT Part No.: JBG110741011
Part Name: RJ45+2USB3.0 ICM(1000Base-T 1Port)

Rev.: C



6. Circuit Schematic and Electronical Specifications:

6-1. Circuit Schematic:



6-2. Electronical Specifications:

- 1.0 Turn Ratio @100KHz: (P2~P3):(J1~J2) = 1:1±5%
(P4~P5):(J3~J6) = 1:1±5%
(P6~P7):(J4~J5) = 1:1±5%
(P8~P9):(J7~J8) = 1:1±5%
- 2.0 Primary Inductance: 350uH MIN @100KHZ,0.1V 8mA DC BIAS
- 3.0 DC Resistance: 1.2 OHMS MAX
- 4.0 Insertion Loss: 1-100MHz -1.0dB MAX
100-125MHz -1.2dB MAX
- 5.0 Return Loss: 1-40MHz -16dB MIN
40-60MHz -12dB MIN
60-80MHz -10dB MIN
80-100MHz -8dB MIN
- 6.0 CROSS TALK: 1-100MHz -30dB MIN
- 7.0 COMMON TO COMMON MODE ATTENUATION: 1-100MHz -30dB MIN
- 8.0 Isolation: PHY Side to Line Side: 2250VDC