









A

B

C

D



NOTES:

ELECTRICAL:

- VOLTAGE RATING : 150 VAC RMS.
- CURRENT RATING : 1.5 AMPS@25°C
- CONTACT RESISTANCE : 20 mΩ Max.
- INSULATION RESISTANCE : 1000 MΩ Min. @500VDC.
- WITHSTAND VOLTAGE : 1000V DC OR AC PEAK;ONE CONTACT TO ALL OTHER CONTACTS CONNECTED TOGETHER @0.5mA 50Hz or 60Hz a minute.

MECHANICAL:

- HOUSING&INSERT MATERIAL : PBT
- CONTACT MATERIAL : PHOSPHOR BRONZE T=0.35mm.
- CONTACT PLATING : 1: CONTACT AREA GOLD PLATING.
2: TAILS PLATING TIN OVER NICKEL.
- MATING/UNMATING FORCE: 20N Max..
- RETENTION STRENGTH : 50N for 60s±5s.
- DURABILITY : 750 CYCLES.
- SEPARATING FORCE : 50N @ 60s±5s.

电气特性:

- 额定电压: 150 VAC RMS
- 额定电流: 1.5 AMPS@25° C
- 接触电阻: 20mΩ Max.
- 绝缘电阻: 1000 MΩ Min.@500 VDC
- 耐压强度: 端子之间: 1000V DC OR AC 峰值

ENVIRONMENTAL:

- STORAGE TEMPERATURE : -40°C~+85°C RELATIVE HUMIDITY<80%
 - OPERATION TEMPERATURE : -40°C~+85°C
 - GUARANTEE PERIOD: 12 MONTHS.
- MATES WITH MODULAR PLUG CONFORMING TO IEC-60603 & TIA-1096

机构特性

- 塑壳材质: PBT;
- 扁针材质: 磷青铜, T=0.35mm;
- 扁针电镀: 接触区镀金
镍底, 剥头电镀雾锡;
- 插入/拔出力: 20N Max.
- 配合强度: 50N for 60s±5s.
- 可靠性: 750次插拔.
- 插芯与塑壳分离力>50N for 60s±5s

环境特性:

- 储存温度: -40°C~+85°C 相对湿度<80%.
- 工作温度: -40°C~+85°C
- 储存时间: 12个月.

10203288A003	5224 1X3 8P8C G/F 窗口面雾面高16.3宽12.7	CZT	无卤PBT黄114C(环保料)
10203288A002	5224 1X3 8P8C G/F 窗口面雾面高16.3宽12.7	CZT	普通PBT黑(环保料)
10203288A001	5224 1X3 8P8C G/F 窗口面雾面高16.3宽12.7	CZT	普通PBT黄114C(环保料)
P/N	DESCRIPTION	商标	MATERIAL COLOR

RoHS Compliant u"=μinch

CZT® 温州意华接插件股份有限公司 WENZHOU YIHUA CONNECTOR CO., LTD				TOLERANCES 公差 00~15 ± 0.15 15~30 ± 0.20 30~ ± 0.25 ANGLES ±1°	Material: 材质 SEE_TABLE	Designed: 设计 Chen Zhiyan	NAME: 名称 RJ45 5224-1*3-8P8C插座高16.3宽12.7
第一视角 A4 SIZE				Finish: 电镀 SEE_TABLE	Checked: 审核	Approved: 核准	DWG NO: 图号 E52190401
SCALE 比例 2:1				UNIT 单位 mm	CUSTOMER: 客户 MODEL NO: 料号	SHEET 第 1 页 共 1 页	PART NO: 料号 SEE TABLE
							REV. 版本 02