



YH-55-32





NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 20 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

1. HOUSING&INSERT& MATERIAL : PBT/PA66/ABS UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE $\phi 0.46$ mm.
3. PLATING : GOLD PLATING OVER NICKEL.
4. MATING/UNMATING FORCE : 30N Max.
5. RETENTION STRENGTH : 50N FOR 60S $\pm$ 5S.
6. OPERATING LIFE : 750 CYCLES MIN.

PC BOARD LAYOUT
THICKNESS=1.6mm

A-A

备注REV16: 新增2.9剥头规格和对应料号

电气特性:

1. 额定电压: 125 VAC RMS
2. 额定电流: 1.5 AMP
3. 接触电阻: 20 m Ω MAX.
4. 绝缘电阻: 1000 M Ω MIN.@500 VDC
5. 耐压强度: 1000 VAC RMS 60Hz, 1分钟

机构特性:

1. 塑壳材质 : PBT/PA66/ABS, UL94V-0;
2. 圆针材质 : 磷青铜, $\phi 0.46$ mm;
3. 圆针电镀 : 镍底, 表面全部镀金;
4. 插入/拔出力 : 30N Max.
5. 配合强度 : 50N 60S $\pm$ 5S .
6. 可靠性: 最少750次插拔.

环境特性:

1. 储存温度: -40 $^{\circ}$ C~+85 $^{\circ}$ C, 0 $^{\circ}$ C~+70 $^{\circ}$ C (ABS) 相对湿度<80%.
2. 工作温度: -40 $^{\circ}$ C~+85 $^{\circ}$ C, 0 $^{\circ}$ C~+70 $^{\circ}$ C (ABS).

ENVIRONMENTAL:

1. STORAGE : -40 $^{\circ}$ C~+85 $^{\circ}$ C, 0 $^{\circ}$ C~+70 $^{\circ}$ C (ABS) RELATIVE HUMIDITY<80%.
2. OPERATION : -40 $^{\circ}$ C~+85 $^{\circ}$ C, 0 $^{\circ}$ C~+70 $^{\circ}$ C (ABS).

MATES WITH MODULAR PLUG CONFORMING TO
FCC PART 68, SUBPART F.

RoHS Compliant

5523 4P (无耳)插座

CZT ® 温州壹华接插件股份有限公司 WENZHOU YIHUA CONNECTOR CO., LTD				TOLERANCES 公差		Material: 材质	SEE_NOTE	Designed: 设计	杨光权	NAME: 名称	RJ22 1X1 5523 4P NO EAR PCB JACK
				00~15 ± 0.15 15~30 ± 0.20 30~ ± 0.25		Finish: 电镀	SEE_NOTE	Checked: 审核		DWG NO: 图号	E55QWY-1009-8
				ANGLES: $\pm 1^{\circ}$		SHEET OF 第1页 共2页		Approved: 核准		PART NO: 料号	SEE_NOTE
										REV. 版本	
										16	

ROHS PART NUMBER:

材质颜色

TIPTOP NUMBER	ERP NUMBER(OLD)	DESCRIPTION	CONTACT PALTING GOLD	MATERIAL COLOR	剥头“A”
10219644B002	B553N-4403-M011	RJ22 1X1 5523 4P4C NO EAR PCB JACK	3u"	PBT BLACK 黑	A=3.3
N/A	B553N-4203-I002	RJ22 1X1 5523 4P2C NO EAR PCB JACK	3u"	ABS GRAY 灰	A=3.3
N/A	B553N-4403-E003	RJ22 1X1 5523 4P4C NO EAR PCB JACK	3u"	ABS BLACK 黑	A=3.3
10219644A007	B553N-44GF-E003	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	ABS BLACK 黑	A=3.3
10219644A003	B553N-44GF-I007	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	ABS DARK GRAY 深灰	A=3.3
10219644A012	B553N-44GF-M011	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	PBT BLACK 黑	A=3.3
10219644A014	B553N-44GF-M015	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	PBT GRAY 灰	A=3.3
10219644F004	B553N-4430-M001	RJ22 1X1 5523 4P4C NO EAR PCB JACK	30u"	PBT BLACK 黑	A=3.3
N/A	B553N-4406-H001	RJ22 1X1 5523 4P4C NO EAR PCB JACK	6u"	ABS BLACK 黑	A=3.3
10219644B001	B553N-4403-F005	RJ22 1X1 5523 4P4C NO EAR PCB JACK	3u"	ABS GRAY 灰	A=3.3
N/A	B553N-4403-I007	RJ22 1X1 5523 4P4C NO EAR PCB JACK	3u"	ABS GRAY 灰	A=3.3
10219644C009	B553N-4406-M001	RJ22 1X1 5523 4P4C NO EAR PCB JACK	6u"	PBT BLACK 黑	A=3.3
10219644D005	B553N-4415-M001	RJ22 1X1 5523 4P4C NO EAR PCB JACK	15u"	PBT BLACK 黑	A=3.3
10219644G002	B553N-4450-M003	RJ22 1X1 5523 4P4C NO EAR PCB JACK	50u"	PBT GRAY 灰	A=3.3
10219644B004	B553N-4403-M015	RJ22 1X1 5523 4P4C NO EAR PCB JACK	3u"	PBT GRAY 灰	A=3.3
N/A	B553N-4450-I007	RJ22 1X1 5523 4P4C NO EAR PCB JACK	50u"	ABS GRAY 深灰	A=3.3
10219644F005	B553N-4430-M003	RJ22 1X1 5523 4P4C NO EAR PCB JACK	30u"	PBT GRAY 灰	A=3.3
10219644D003	B553N-4415-M003	RJ22 1X1 5523 4P4C NO EAR PCB JACK	15u"	PBT GRAY 灰	A=3.3
10219642A001	B553N-42GF-M003	RJ22 1X1 5523 4P2C NO EAR PCB JACK	G/F	PBT GRAY 灰	A=3.3
N/A	B553N-4315-M001	RJ22 1X1 5523 4P3C(2.3.4) NO EAR PCB JACK	15u"	PBT GRAY 灰	A=3.3
10219644A010	B553N-44GF-M018	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	PBT WHITE 白	A=3.3
10219644C008	B553N-4406-U002	RJ22 1X1 5523 4P4C NO EAR PCB JACK	6u"	PA66B30 BLACK 黑	A=3.3
10219644A008	B553N-44GF-F005	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	ABS GRAY 灰	A=3.3
10219644F006	B553N-4420-M001	RJ22 1X1 5523 4P4C NO EAR PCB JACK	钯金20u"	PBT BLACK 黑	A=3.3
10219644B006	B553N-4403-U002	RJ22 1X1 5523 4P4C NO EAR PCB JACK	3u"	PA66B30 BLACK 黑	A=3.3
10219644C011	B553N-4406-M003	RJ22 1X1 5523 4P4C NO EAR PCB JACK	6u"	PBT GRAY 灰	A=3.3
10219644G003		RJ22 1X1 5523 4P4C NO EAR PCB JACK	50u"	PBT BLACK 黑	A=3.3
10219644A006	B553N-44GF-G004	RJ22 1X1 5523 4P4C NO EAR PCB JACK	G/F	ABS WHITE 康达白	A=3.3
10219644D007		RJ22 1X1 5523 4P4C NO EAR PCB JACK(剥头2.9)	15u"	PBT BLACK 黑	A=2.9

RoHS Compliant

5523 4P (无耳)插座

CZT® 温州竟华接插件股份有限公司 WENZHOU YIHUA CONNECTOR CO.,LTD				TOLERANCES 公差 00~15 ±0.15 15~30 ±0.20 30~ ±0.25	Material: 材 质	SEE_NOTE	Designed: 设 计	杨光权	NAME: 名 称	RJ22 1X1 5523 4P NO EAR PCB JACK	
					Finish: 电 镀	SEE_NOTE	Checked: 审 核		DWG NO: 图 号	E55QWY-1009-8	REV. 版本
				ANGLES: ±1°	SHEET OF 第 2 页 共 2 页		Approved: 核 准		PART NO: 料 号	SEE_NOTE	16