




- 机构特性:

- | REV.
版本 | ECN NO.
变更说明 | DATE
日期 |
|------------|-----------------|------------|
| 01-04 | ADD PART NO. | |
| 05 | 图号合并 | 2009.05.25 |
| 06 | 增加易飞 | 2009.12.01 |
| 07 | 增加易飞 | 2012.02.24 |



环境特性:

- 图 12 为 12 个月。
-

PC BOARD LAYOUT
THICKNESS=1.6mm

NOTES:

ELECTRICAL:

- | | | |
|--------------------------|---|---|
| 1. VOLTAGE RATING | : 150 VAC RMS. | 5 |
| 2. CURRENT RATING | : 1.5 AMP. | |
| 3. CONTACT RESISTANCE | : 20 MILLIOHMS MAX. | |
| 4. INSULATION RESISTANCE | : 1000 MEGOHMS MIN @ 500 VDC | |
| 5. DIELECTRIC STRENGTH | : CONTACT TO CONTACT:1000 V DC OR AC PEAK | |
| | : CONTACT TO SCREEN AND TEST PANEL:1500 V DC OR AC PEAK | |
| MECHANICAL : | : @ 0.5mA 50 Hz OR 60 Hz A MINUTE | |

MECHANICAL:

- | | |
|-------------------------------|--------------------------------------|
| 1. HOUSING&INSERT& MATERIAL : | SEE TABLE UL94V-0. |
| 2. CONTACT MATERIAL | PHOSPHOR BRONZE Ø0.46mm. |
| 3. PLATING | GOLD PLATING OVER NICKEL. |
| 4. SHIELD | BRASS T=0.2mm PLATED NICKEL FOR ALL. |
| 5. OPERATING LIFE | 750 CYCLES MIN. |
| 6. MATING/UNMATING FORCE: | 30N Max. |
| 7. RETENTION STRENGTH: | 50N FOR 60S±5S. |

ENVIRONMENTAL:

1. STORAGE : -40°C TO +85°C RELATIVE HUMIDITY<80%.
2. OPERATION : -40°C TO +85°C.
3. GUARANTEE PERIOD: 12 MONTHS.

MATES WITH MODULAR PLUG CONFORMING TO IEC-60603 & TIA-1096


ROHS PART NUMBER:

	PART NUMBER	PART NUMBER(OLD)	DESCRIPTION	CONTACT PALTING GOLD	HOUSING&INSERT MATERIAL	BACK METAL PE
		B591S6-1803-U002	5921S 6PQRTS 10P8C PCB JACK W/ CZT	3U'	PA66 BLACK	3
△		B591S6-1815-M001	5921S 6PQRTS 10P8C PCB JACK W/O LOGO	15U'	PBT BLACK	3
△	10230518C002	B591S6-1806-M001	5921S 6PQRTS 10P8C PCB JACK W/O LOGO	6U'	PBT BLACK	3
△	10230518A002	B591S6-18GF-M008	5921S 6PQRTS 10P8C PCB JACK W/O LOGO	G/F	PBT BLACK	3
△	10230518A003	B591S6-18GF-M007	5921S 6PQRTS 10P8C PCB JACK W/O LOGO	G/F	PBT BLACK	1
△		B591S6-1806-M003	5921S 6PQRTS 10P8C PCB JACK W/O LOGO	6U'	PBT BLACK	0
△	10230518B001	B591S6-1803-M007	5921S 6PQRTS 10P8C PCB JACK W/O LOGO	3U'	PBT BLACK	1
	10230518B002		5921S 6PQRTS 10P8C PCB JACK W/O LOGO	3U'	PBT BLACK	0

RoHS Compliant

△5 取消图号: QWY-1012-23/Q07111903/Q07111904/QWY-1081-18/QWY-1140-4/QWY-1081-15/E5900016

5921S 六胞 包壳插座

 温州意华接插件股份有限公司 WENZHOUI YIHUA CONNECTOR CO., LTD				TOLERANCES 公差 00~15 ±0.15 15~30 ±0.20 30~ ±0.25		Material: 材 质 SEE NOTE		Designed: 设 计 刘 攀		NAME: 名 称 RJ 5921S 6PORTS PCB JACK	
 第一视角		A4 SIZE		SCALE 比 例 1:1		UNIT 单 位 mm		CUSTOMER: 客 户 N/A		MODEL NO: 料 号 N/A	
				ANGLES: ±1°		Finish: 电 镀 SEE NOTE		Checked: 审 核		DWG NO: 图 号 E5900012	
						SHEET 1 OF 1 第 页 共 页		Approved: 核 准		PART NO: 料 号 SEE NOTE	
										07	