

NOTE:

An exploded view diagram of the front panel assembly. It shows three main components: a front panel with a circular cutout at the bottom, a bezel with a USB symbol, and a mounting bracket with a screw. The components are shown in a perspective view, with the front panel at the bottom, the bezel in the middle, and the mounting bracket at the top.

- 1.Voltage Rating:12V DC
- 2.Current Rating:POWERED 3AMP USB 1AMP
- 3.Insulation Resistance:1000M Ω Min.
- 4.Contact Resistance:30m Ω Max.
- 5.Dielectric Withstanding Voltage:100V AC
- 6.Temperature Range:-25°C to +85°C
- 7.Mechanical Characteristics:
Insertion Force:35N Max.
Extraction Force:10N Min.

SEARIS NO.

CONTACT PLATING:

A=G/F B=3u " C=6u " D=15u " F=30u "

CZT[○] DONGGUAN ZHENGDE (YIHUA) CONNECTOR CO., LTD

X. ± 0.38	X. $\pm 4^{\circ}$	UNIT:	mm	DR:	GB_Zeng	TITLE: Powered USB Male Pos.1 12V	D/N: 6308-0001	M/N:
.X ± 0.25	.X $\pm 2^{\circ}$	3RD:		DE:	GB_Zeng			
.XX ± 0.20	.XX	SCALE:	1 : 1	CHKD:				
.XXX ± 0.10	.XXX	CUSTOMER DRAWING	REV:	A-0	APPD:			